# **SAFETY DATA SHEET**

## 1. Identification

Product number 1000009806
Product identifier Ink Anti-Skin

Company information FUJIFILM GRAPHIC SYSTEMS

200 Summit Lake Drive

Valhalla, NY 10595 United States

Emergency telephone US

Emergency telephone outside

US

1-866-836-8855 1-952-852-4646

Version # 01
Recommended use Coating
Recommended restrictions None known.

# 2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSerious eye damage/eye irritationCategory 2ASensitization, skinCategory 1

Carcinogenicity Category 2
Reproductive toxicity (fertility) Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

Aspiration hazard Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. May cause an allergic

skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility. May cause damage to organs through prolonged

Category 2

or repeated exposure.

**Precautionary statement** 

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear

protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash

with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye

irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Environmental hazards** Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment,

long-term hazard

Hazard(s) not otherwise

classified (HNOC)

Combustible.

Supplemental information

None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	20 - 40
Distillates (Petroleum), Hydrotreated Light		64742-47-8	10 - 20
Isopropyl Alcohol		67-63-0	10 - 20
Propane		74-98-6	10 - 20
Butylated Hydroxytoluene		128-37-0	2.5 - 10
n-Hexane		110-54-3	2.5 - 10
Cyclohexane		110-82-7	0.1 - 1
Methyl Ethyl Ketoxime		96-29-7	0.1 - 1
Other components below reporta	ble levels		10 - 20

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact eczema or other skin disorders. Seek medical attention and take along these instructions.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

Eye contact present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth, Do not induce vomiting, If

Category 2

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

media

Ingestion

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards

Extremely flammable aerosol. Combustible.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)** 

Components	Type	Value	
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3	
		300 ppm	
Isopropyl Alcohol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m3	
		500 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Value	S		
Components	Туре	Value	Form
Butane (CAS 106-97-8)	STEL	1000 ppm	
Butylated Hydroxytoluene (CAS 128-37-0)	TWA	2 mg/m3	Inhalable fraction and vapor.

Product name: Ink Anti-Skin

Product #: 1000009806 Version #: 01 Issue date: 04-20-2017

SDS US

Components	Туре	Value Form	
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm	
,	TWA	200 ppm	
n-Hexane (CAS 110-54-3)	TWA	50 ppm	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Butylated Hydroxytoluene (CAS 128-37-0)	TWA	10 mg/m3	
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3	
,		300 ppm	
Isopropyl Alcohol (CAS 67-63-0)	STEL	1225 mg/m3	
,		500 ppm	
	TWA	980 mg/m3	
		400 ppm	
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3	
		50 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
US. Workplace Environmental Exp	osure Level (WEEL) Guides		
Components	Type	Value	
Methyl Ethyl Ketoxime (CAS 96-29-7)	TWA	36 mg/m3	
•		10 ppm	
		* *	

## **Biological limit values**

**ACGIH Biological Exposure Indices** 

Components	Value	Determinant	Specimen	Sampling Time
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

# **Exposure guidelines**

US - California OELs: Skin designation

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide

eyewash station.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Product name: Ink Anti-Skin
Product #: 1000009806 Version #: 01 Issue date: 04-20-2017

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

**Appearance** 

Physical state Gas.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point -156.0 °F (-104.4 °C) PROPELLANT estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.5 % estimated

12 % estimated

(%)

Flammability limit - upper

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 50 psig @70F estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 0.696 estimated

VOC (Weight %) 80.8 % estimated

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Keep away from heat, sparks and open flame. Avoid temperatures exceeding the flash point.

Contact with incompatible materials.

**Incompatible materials** Acids. Strong oxidizing agents. Nitrates. Isocyanates. Fluorine. Chlorine.

Hazardous decomposition

Conditions to avoid

products

No hazardous decomposition products are known.

Product name: Ink Anti-Skin

# 11. Toxicological information

# Information on likely routes of exposure

**Inhalation** May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

drowsiness and dizziness. Headache. Nausea, vomiting.

**Skin contact** May cause an allergic skin reaction.

**Eye contact** Causes serious eye irritation.

**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

#### Information on toxicological effects

May be fatal if swallowed and enters airways. Narcotic effects. May cause an allergic skin **Acute toxicity** reaction. Components **Species Test Results** Butane (CAS 106-97-8) **Acute** Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes Rat 1355 mg/l Butylated Hydroxytoluene (CAS 128-37-0) Acute **Dermal** LD50 Rat > 2000 mg/kg > 2000 mg/kg, 4 wk (3 x/wk)Oral LD50 Mouse 2000 mg/kg Rat > 2930 mg/kg

Cyclohexane (CAS 110-82-7)

Acute Dermal

LD50 Rabbit

Inhalation

LC50 Rat > 32880 mg/m3, 4 Hours

> 5540 ppm, 4 Hours

> 2000 mg/kg

Oral

LD50 Rabbit > 5000 mg/kg
Rat > 5000 mg/kg

Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)

**Acute** 

Dermal

LD50 Rabbit > 2000 mg/kg

> 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat > 7.5 mg/l, 6 Hours

> 4.6 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Components Species Test Results

Isopropyl Alcohol (CAS 67-63-0)

**Acute** 

**Dermal** 

LD50 Rabbit 16.4 ml/kg, 24 Hours

Inhalation

LC50 Rat > 10000 ppm, 6 Hours

Oral

LD50 Rat 5.84 g/kg

Methyl Ethyl Ketoxime (CAS 96-29-7)

Acute Dermal

LD50 Rabbit > 1000 mg/kg, 24 Hours 0.2 - 2 ml/kg, 24 Hours

Inhalation

LC50 Rat > 10.5 mg/l, 8 Hours > 4.83 mg/l, 4 Hours

Oral

LD50 Rat > 900 mg/kg

n-Hexane (CAS 110-54-3)

Acute Dermal

LD50 Rabbit > 2000 mg/kg, 4 Hours

> 5 ml/kg, 4 Hours

Inhalation

LC50 Rat > 5000 ppm, 24 Hours

> 31.86 mg/l

73860 ppm, 4 Hours

Oral

LD50 Rat 24 ml/kg

24 g/kg

Wistar rat 49 g/kg

Propane (CAS 74-98-6)

Acute Inhalation

LC50 Mouse 1237 mg/l, 120 Minutes

52 %, 120 Minutes

Rat 1355 mg/l

658 mg/l/4h

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Suspected of causing cancer.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

# IARC Monographs. Overall Evaluation of Carcinogenicity

Butylated Hydroxytoluene (CAS 128-37-0)

3 Not classifiable as to carcinogenicity to humans.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

# US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

Suspected of damaging fertility.

Specific target organ toxicity -

May cause drowsiness and dizziness.

single exposure

Specific target organ toxicity -

repeated exposure

Respiratory system. Skin. Central nervous system. Eyes. Peripheral nervous system. May cause

damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways. **Aspiration hazard** 

**Chronic effects** May cause damage to organs through prolonged or repeated exposure.

# 12. Ecological information

Toxic to aquatic life with long lasting effects. **Ecotoxicity** 

utylated Hydroxytoluene (CAS 128-37-0)	
Aquatic	
Algae IC50 Algae	6 mg/L, 72 Hours
Crustacea EC50 Water flea (Daphnia pulex)	1.44 mg/l, 48 hours
yclohexane (CAS 110-82-7)	
Aquatic	
Fish LC50 Fathead minnow (Pimephales promelas)	23.03 - 42.07 mg/l, 96 hours
stillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)	
Aquatic	
Fish LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
opropyl Alcohol (CAS 67-63-0)	
Aquatic	
Algae IC50 Algae	1000.0001 mg/L, 72 Hours
Crustacea EC50 Daphnia	13299 mg/L, 48 Hours
Fish LC50 Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours
ethyl Ethyl Ketoxime (CAS 96-29-7)	
Aquatic	
Algae IC50 Algae	83 mg/L, 72 Hours
Crustacea EC50 Daphnia	750 mg/L, 48 Hours
Fish LC50 Fathead minnow (Pimephales promelas)	777 - 914 mg/l, 96 hours
Hexane (CAS 110-54-3)	
Aquatic	
Fish LC50 Fathead minnow (Pimephales promelas)	2.101 - 2.981 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

## **Bioaccumulative potential**

## Partition coefficient n-octanol / water (log Kow)

Butane	2.89
Cyclohexane	3.44
Isopropyl Alcohol	0.05
n-Hexane	3.9
Propane	2.36

No data available. Mobility in soil

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

## 14. Transport information

DOT

UN number UN1950

**UN proper shipping name** Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisionsN82Packaging exceptions306Packaging non bulkNonePackaging bulkNone

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** Yes **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

Packaging Exceptions LTD QTY

**IMDG** 

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Product name: Ink Anti-Skin
Product #: 1000009806 Version #: 01 Issue date: 04-20-2017

Packing group

**Environmental hazards** 

Not applicable.

Marine pollutant

Yes

F-D. S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

LTD QTY

the IBC Code

DOT



IATA; IMDG



Marine pollutant



**General information** IMDG Regulated Marine Pollutant.

# 15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US federal regulations** 

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Cyclohexane (CAS 110-82-7) Listed. n-Hexane (CAS 110-54-3) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

# SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
n-Hexane	110-54-3	2.5 - 10	_
Cyclohexane	110-82-7	0.1 - 1	

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

n-Hexane (CAS 110-54-3)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

## **US state regulations**

## US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Butane (CAS 106-97-8)

Isopropyl Alcohol (CAS 67-63-0)

n-Hexane (CAS 110-54-3)

#### **US. Massachusetts RTK - Substance List**

Butane (CAS 106-97-8)

Butylated Hydroxytoluene (CAS 128-37-0)

Cyclohexane (CAS 110-82-7) Isopropyl Alcohol (CAS 67-63-0) n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

## US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)

Butylated Hydroxytoluene (CAS 128-37-0)

Cyclohexane (CAS 110-82-7)

Isopropyl Alcohol (CAS 67-63-0)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

## US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)

Butylated Hydroxytoluene (CAS 128-37-0)

Cyclohexane (CAS 110-82-7)

Isopropyl Alcohol (CAS 67-63-0)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

## US. Rhode Island RTK

Butane (CAS 106-97-8)

Cyclohexane (CAS 110-82-7)

Isopropyl Alcohol (CAS 67-63-0)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

## **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

## US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997 Toluene (CAS 108-88-3) Listed: January 1, 1991 US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

# 16. Other information, including date of preparation or last revision

04-20-2017 Issue date

Version # Λ1

The information provided in this Safety Data Sheet is correct to the best of our knowledge, Disclaimer

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision information** This document has undergone significant changes and should be reviewed in its entirety.

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).